

# Alcatel-Lucent Enterprise MK20 Audio and Video Meeting Kit

## Plug-and-play installation & superior audio and video quality

The ALE MK20 liftable audio and video conferencing device integrates 4 omnidirectional microphones and a 1080P camera with a 120-degree field of view. Compatible with mainstream Unified Communications (UC) software, ALE MK20 can be powered via the USB connection and supports plug and play.

The built-in noise reduction technology combined with a high-definition camera and vertically adjustable wide-angle lens enables the conferencing device to provide a superior audio and video experience for end users. Making remote conferences productive as well as engaging, ALE MK20 is a great choice for home office, huddle rooms or small meeting rooms.



### Highlights

- Clear audio and premium video quality
- Plug and play
- Ideal for home office, huddle rooms or small meeting rooms

### Technical Specifications

#### Physical Characteristics

- Dimension:  $\phi 76 \times 260$ mm
- Weight: 730 g
- Color: Gray

#### Keys & LED

- 4 sensitive keys: Volume increase (+)/decrease (-), microphone mute, and speaker mute
- Blue LED on for working mode
- Red LED on for microphone mute
- Blue LED flashing for speaker mute & volume adjustment

#### Audio Characteristics

- Omnidirectional microphone x 4
- 4 $\Omega$ 5w antimagnetic speaker
- Pickup: 48k sampling rate

- Playback: 48k sampling rate
- Volume: Instantaneous up to 90dB
- Echo cancellation, automatic gain control
- Full duplex
- Intelligent dynamic noise reduction

#### Video Characteristics

- Fixed focus, 120° FOV(H)
- CMOS sensor, 1/2.7"
- 1080P (1920\*1080)

#### Connectivity

- USB 2.0 (full speed)
- Powered by USB (5V500mA)

#### Supported Systems

- Windows 7/8.1/10
- Mac OS 10.12 and above

#### EMC

- EN 55032:2015, EN 55035:2017
- 47 CFR Part 15 B Subpart B

#### Eco Design

- WEEE 2012/19/EU
- ROHS 2011/65/EU, China RoHS 2.0: GBT 26572-2011
- REACH (EC1907/2006)
- Proposition 65

#### Environmental Conditions

- Operating temperature: 0°C to +44°C
- Relative humidity: 20% to 85%
- Storage/transportation temperature: -10°C/+55°C

#### Packaging

- ALE MK20 x1
- USB Cable x1
- Quick User Guide x1